NORO



LAKE SHOWER CABIN 80X80 C

Item number: 66020

Supplied with 3-function shower set. Magnet function when closing. Spring loaded wheels with ball bearing. Suitable for mixers cc 150 and 160 mm for cubicle lead-through ½. 5 mm safety glass. Aluminium profile. Tray in glass fibre reinforced acrylic. Rear walls in glass with a discrete structure, conceals underlying pipe.

Included articles

2434 1 x lake tray 80x80c
 2435 1 x lake back walls 80x80c
 2436 1 x lake door 80x80c

Detailed information

Item number		Material and surface treatmen	t
NOBB	53440872	Main material	PU reinforced acrylic, Safety
RSK	7365752	Surface treatment	glass, Aluminum Anodized
EAN	7340032403145	Glass	Clear glass
Standards and classifications		Color	Aluminum
EN standard	EN14428, EN14527	Packaging dimensions and weight Package width (m) 1,970	
CE marked	Yes		
ETIM	EC010491	Package height(m)	0,900
Product dimensions and weight		Package depth(m)	0,870
Height (mm)	2040	Package weight(kg)	94,600
Height min. (mm)	2025		,,,,,
Height max. (mm)	2045		
Width	800		
Depth (mm)	800		
Glass thickness (mm)	5		
Net weight (kg)	88,3		

Care instructions

To facilitate the cleaning of shower doors and shower walls, the showers have large smooth surfaces and profiles without deep grooves. Discolouration is removed using citric or tartaric acid, rinse thoroughly afterwards. Limescale stains are removed using household vinegar warmed to 50 degrees: Rub it in, let it act, rinse away. Repeat for tough stains. Use rubbing alcohol to remove grease stains.